

LS490YXS-EF

49" Full-HD Video Wall Display Unit (Narrow Bezel 11.8mm)



Features:

- 11.8mm narrow bezel LCD splicing unit.
- Industrial level wide viewing angle panel, suitable for extensive 7×24 continuous works.
- Full high definition resolution, high image quality, and no light-leaking.
- Built-in 3D COMB filter and 3D Noise Reduction.
- Built-in automatic ghost elimination function to protect the long-term use of LCD screen.
- Professional thermal design to extend equipment lifespan.
- Abundant interfaces HDMI, DVI, VGA, BNC, support video loop.
- Infrared, software control, supporting remote PC control.
- Brightness smart detection, power-saving.



Technical Specification

Model

Model	LS490YXS-EF
-------	-------------

System

Diagonal	49"(16:9)
Resolution	1920×1080 (FHD)
Backlight	LED
Brightness/Luminance (Standard)	380 cd/m ²
Contrast	1200:1
Angle of view	176°/176°(vertical/horizontal)

Video Signals

Input	Standard	VGA(D-Sub)×1, CVBS(BNC)×2, DVI-D×1, HDMI×1, RS232×1, USB×1
	Optional	Audio×1, RJ45×1, HDCVI×1, SDI×1, DP×1
Output	Standard	CVBS(BNC)×2, RS232×1
	Optional	Audio×1, DP×1

General

Consumption (Standard)	70W
Consumption (Standby)	≤1W
Power Supply	AC100~240V (±10%), 50/60Hz

Net Weight	13.0kg
Dimensions (with frame)	1090.40mm×621.30mm×45.50mm
VESA	400×400
Installation Mode (all optional)	Wall-mounted, Base installation
Control signal	Infrared, RS232 double mode, supporting remote PC control
Work Environment	Temperature: 0 C~50 C
	Humidity: 20%~90%

Accessory

Standard	VGA cable, power cable, remote control
Optional	Pedestal, hanging bracket

Dimensions(mm)

