

# DH-PFS3409-4GT-96

9-Port Gigabit Switch with 4-Port PoE (Unmanaged)



## Product Overview

DH-PFS3409-4GT-96 is a layer two Hardened PoE Switch, which provides 4 \*10/100/1000Mbps PoE ports, 4 \*1000Mbps optical ports and 1\* 10/100/1000Mbps Ethernet uplink port. With high level lightning protection and wide working temperature range makes it a better performance in outdoor or harsh environment.

## Features

- Layer 2 Hardened Ethernet switch
- MAC auto study and aging, MAC address list capacity is 4K
- Support IEEE802.3af, IEEE802.3at and Hi-PoE standard
- Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards
- Adopts metal structure
- Industrial wide working temperature design: -30°C~+65°C
- High protection grade, supports common mode 4KV, differential mode 2KV
- Supports dual power backup

## Technical Specification

Model	DH-PFS3409-4GT-96
Ethernet Port	4*10/100/1000 Mbps Base-T (PoE power supply) 1*10/100/1000 Mbps Base-T uplink 4*1000Mbps Base-X
Switching Capacity	33Gbps
Packet Forwarding Rate	13.39Mpps
Packet Buffer Memory	1.75Mb
MAC Table Size	4K
Flow Control	Enable by default
Application Humidity	10%~90%
Power	DC48~57V
Lightning Protection	Common Mode 4KV Differential Mode 2KV
ESD	Contact discharge: ±6kV Air discharge: ±8kV
Working Temperature	-30°C~65°C
Weight	0.62kg
Dimension(WxDxH)	150mm×110mm×42mm

## Accessories

Model	
PFT3950	1.25G 850nm,500m,LC, Multi-mode
PFT3960	1.25G 1310/1550nm,20km,LC, Single-mode
PFT3970	1.25G 1550/1310nm,20km,LC, Single-mode